## This Page Is Inserted by IFW Operations and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

# THIS PAGE BLANK (USPTO)

#### Europäisches Patentamt European Patent Office Office européen des brevets

(11)

EP 1 022 906 A1

(12)

#### **EUROPEAN PATENT APPLICATION**

(43) Date of publication: 26.07.2000 Bulletin 2000/30

(51) Int. Cl. 7:

**H04N 7/18**, D21G 9/00

- (21) Application number: 00660009.2
- (22) Date of filing: 19.01.2000
- (84) Designated Contracting States:

  AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU

  MC NL PT SE

  Designated Extension States:


  AL LT LV MK RO SI
- (30) Priority: 22.01.1999 FI 990120
- (71) Applicant: Hildeco OY Ltd. 40100 Jyväskylä (FI)
- (72) Inventors:
  - Valkonen, Mika
     44100 Äänekoski (FI)
  - Snellman, Jorma
     40900 Säynätsalo (FI)
  - Toivonen, Juha
     40200 Jyväskylä (FI)
- (74) Representative: LEITZINGER OY Ruoholahdenkatu 8 00180 Helsinki (FI)
- (54) System for monitoring a process
- (57) The invention relates to a method for monitoring a process. The image information received from cameras monitoring various positions of the process is stored in digital form and various cameras positions are alternately selected for a display and analysis on the screen of a computer. The screen is also used for displaying an image variation graph representing the image variation data of images preceding and following the image to be analyzed. The system includes selector elements (5) for selecting a camera position representing the highest-level image variation for an automated display.

9

0

တ

0



#### Description

5

20

25

30

35

40

45

50

55

[0001] The present invention relates to a method for monitoring a process, said system comprising

- a number of cameras for imaging various positions in a presently monitored process;
- digital image processors for storing digital image information as per camera and for analyzing each camera-specific image information so as to provide image variation data based on the level of variation in several sequential images; and
- a display or screen which can be used for selecting images stored from various camera positions for analysis, while using the screen for displaying an image variation graph representing the image variation data of images preceding and following the image to be analyzed.

[0002] In a particular application of the invention, the process comprises papermaking and the monitored object comprises a paper web traveling in a paper machine.

[0003] Prior to the present invention, the system designed by the Applicant has been operated by using software for selecting a given break in a paper web for analysis, wherefor the system displays all stored icons of camera positions on the analyzing window of a computer screen (fig. 2 shows a printout of this window). In addition, the image material of all camera positions is used for composing an image variation graph 8 (one for each camera position) visible at the bottom of the picture shown in fig. 2, which represents image variation data based on the level of variation in sequential images. The user selects his or her chosen camera position by means of selector icons 7. Thus, the user is compelled to examine several different camera positions and to compare those with each other prior to being able to locate image data representing the highest-level variation and an image variation graph consistent therewith.

[0004] It is an object of the invention to provide an improved system, wherein the image—variation graph representing the highest-level variation and the image data of a camera position consistent therewith can be selected automatically for display on an analyzing window. This object is achieved by the invention on the basis of the characterizing features set forth in the annexed claim 1. One exemplary embodiment of the invention will now be described in more detail with reference to the accompanying drawings, in which

fig. 1 shows a system of the invention in a block diagram, and

fig. 2 shows an analyzing window present on a computer screen in the system, whereby the user is able to analyze a process variation incident.

[0005] An image source in the block diagram of fig. 1 comprises a video camera 1, which produces continuously a video image of a presently monitored object. The image information is processed in a digital signal processor 2 or a DSP processor (digital signal processor). The signal processors are like ordinary microprocessors, but contain a.o. the service of floating-point number technology and address formats for easier addressing. Furthermore, the DSP is markedly different from the ordinary processor in terms of its architecture, having been designed for duties involving plenty of data, and in which multiplying with integers and data transfers are statistically significant operations. The DSP processors are capable of performing a plurality of different and simultaneous calculation routines associated with image analysis, the results of which can be applied automatically to monitoring changes or variations occurring in image information.

[0006] The system includes a number of video cameras 1 for imaging various positions of a presently monitored process. Each camera is provided with its own separate image processor 2 for storing digital image information as per camera. The signal processors 2 are used for analyzing each camera-specific image information so as to provide image variation data based on the level of variation in a plurality of sequential images. From the signal processors 2, said image data and image variation data is transmitted to an analyzing computer, having a display or screen 11 which is shown more specifically in fig. 2.

[0007] The icons 7 visualized in fig. 2 can be used for choosing images stored at various camera positions for analysis. The image variation graph 8 consistent with the image variation data of images preceding and following the image to be analyzed is displayed at the bottom of the screen. A floating arrow designated by reference numeral 9 indicates the point along the image variation graph 8 that a displayed image 10 is located at. The floating arrow 9 can be used for selectively displaying any image present along the graph 8. The image data stored from each camera position may encompass several hundred images. Depending on a process, the image data in store at any given moment of time may have a duration which ranges from a few seconds to several minutes, and the storage may function on a FIFO (first in first out) principle.

[0008] Since it is the image material from all camera positions which is used for composing the image variation graph 8 visible at the bottom of fig. 2, the image variation graphs of various camera positions can be made comparable

#### EP 1 022 906 A1

by standardization and be compared with each other, whereby the image variation graph representing the highest-level variation and the image data of a camera position consistent therewith can be automatically chosen to be displayed on the analyzing window of the screen 11. For the purpose of this automation, the system is provided with stardardizing devices 3 for standardizing the output levels of the image variation data of various camera positions to be mutually comparable. A comparison between the image variation levels of various camera positions is performed by means of comparator elements 4. Selector elements 5 receive image data from various camera positions and choose, under the control of the comparator elements 4, image data 6 representing the highest-level variation and the corresponding image variation graph 8 to be displayed on the screen 11. An image 10 is one of a multitude of images included in the image data. The graph 8 and the floating indicator 9 can be used for examining those very images 10 associated with the site of the highest-level image variation. In the exemplary case of fig. 2, the image 10 on the screen 11 represents a hole developed in a paper web.

Naturally, the automated selection of the invention is such that, according to his or her wishes, the user is able to choose image data from any camera position for analysis. However, it is often beneficial that the user has knowledge at the very beginning of analysis as to which camera position produced the highest-level image variation, whereby the analysis can be started from this particular camera position.

5

10

15

20


25


35

- Claims
- 1. a method for monitoring a process, said system comprising
- a number of cameras (1) for imaging various positions in a presently monitored process;
  - digital image processors (2) for storing digital image information as per camera and for analyzing each cameraspecific image information so as to provide image variation data based on the level of variation in several sequential images; and
  - a display or screen (11) which can be used for selecting images (10) stored from various camera positions for analysis, while using the screen (11) for displaying an image variation graph (8) representing the image variation data of images preceding and following the image (10) to be analyzed,
- characterized in that the system comprises 30
  - stardardizing devices (3) for standardizing the output levels of the image variation data from various camera positions to be mutually comparable;
  - comparator elements (4) for a mutual comparison between the standardized image variation levels from various camera positions; and
    - selector elements for selecting the camera position with the highest-level image variation for automated display;
- said selector elements (5) being in communication with the digital image processors (2) for receiving image data 40 from various camera positions, and said comparator elements (4) being adapted to control the selector elements (5) in such a way that the image data representing the highest-level variation and the image variation graph (8) consistent therewith are selected for an automated display on the screen (11).
- 2. A system as set forth in claim 1, characterized in that the process comprises papermaking and the object of 45 monitoring comprises a paper web traveling in a paper machine.

50

55







### **EUROPEAN SEARCH REPORT**

Application Number

EP 00 66 0009

	DOCUMENTS CONSIDERED TO BE RELEVANT  Citation of document with indication, where appropriate,  Relevant				ļ	
Category	of relevant pa	n indication, where appr ssages	opriate,	Relevant to claim	CLASSIFICAT APPLICATION	
Y	US 5 239 376 A (B AL) 24 August 199 * column 1, line * column 3, line * column 5, line * abstract * * figures 1,2A,2C	3 (1993-08-24) 7 - line 20 * 14 - line 18 * 24 - line 34 *	AM L ET	1,2	H04N7/18 D21G9/00	
	US 5 011 573 A (N) 30 April 1991 (199 * figure 4 * * column 2, line 2 * column 5, line 4	91-04-30) 26 - line 63 *	line 15 *	1,2		
	US 5 821 990 A (RU 13 October 1998 (1 * column 1, line 6 * figure 1 *	.998-10-13)	•	1,2		
	WO 98 46826 A (ENS (FI); KAARTA HARRI () 22 October 1998 * page 1, line 16 * page 3, line 4 - * figure 1 *	(FI); HAEKKIN (1998-10-22) page 2. line	EN MARKKU	1,2	TECHNICAL F SEARCHED H04N D21G D21F	FIELDS (Int.Cl.7)
	The present search report has	been drawn up for all cl	aims			
	Place of search	Date of comple	tion of the search		Examiner	
1	HE HAGUE	15 May	2000	Tito	Martins,	J
X : particu Y : particu documi A : techno O : non-wr	EGORY OF CITED DOCUMENTS larly relevant if taken alone larly relevant if combined with anot ant of the same category logical background itten disclosure diate document	E her D L	theory or principle earlier patent docu after the filing date document ofted in document ofted for member of the san document	underlying the inv iment, but publish the application other reasons	ention ed on, or	

#### ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 00 66 0009

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-05-2000

FORM P0459